All rights reserved to SMS. With it, duplication of this document, and giving it to others, and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights created by the grant of a patent or the registration of a utility model or design.

(824)
(112) (600) Ballenlänge (112)
ROLL BARREL LENGTH
(85) (60) (60) (60) (70) (60) (60) (60) (85) Gerüst 13 MILL STAND 13 轧机
(192) max. Verschiebung 256
MAX. SHIFTING 最大移动
(76) (64) (64) (64) (64) (64) (64) (64) (76) Gerüst 11 MILL STAND 11 轧机

(375) 500 375
(102) 222 602 222 (102)
80 192 440 192 ø47
110 110 (92) 256 (92)
296
28 F9 (+0.04 +0.02) 4 M16 G1
R0.8 B 6.2 R0.6 12 25 18 28
(105) 25 R1 50
(15) (15) ø28
170 456 245 510
405
ø50 ø50
3 25 25 30 25
PIPE Rohr 60,3x2,9 DIN 2448
4 T60,3x2,9-42,4x2,6 DIN 2615-2 St37.0
5 St37.0 4 St37.0
3 3 3 3
135 205
25
10 2x
09
1
05 06
A A
10 11 12
10 Muffe G2 DIN 2986 St SLEEVE 套
116 128 116
(445) 360 445
1250

480
256 (188)
15 420
30 180 180
Mitte Ständer MILL HOUSING 轧机机架
Mitte Ständer MILL HOUSING 轧机机架
25 K3
70
(11) (65) (65)
220 3-ø22
4 M10x9/17
25 K1 K1 25
55
25 25
02 04 03 04
12x45°
440
500
2-M10x9/17

A-A
(445)
220 70
(225) (290)
Walzen ø 330 MILL ROLL DIAMETER (90) 190
Walzmitte PASS LINE 轧制线
70 ø8 114 33
15 28 3.2 3.2
(135) 11 40.2 K1 2 Bezugsfläche DATUM SURFACE 基准面
25 25 R0.6 12x45°
Bezugsfläche DATUM SURFACE 基准面
60 ø15 3 75 160
07 08 70 25 25 25 25 40 20 25 20° 170
(90) 222 25 25 25 90°
65 30° 42x5 Rohr 42,4x2,6 DIN 2448 PIPE St37.0 管
445 405 380
9 6x Muffe G3/4 DIN 2986 SLEEVE St 套
7 2x
80 57
6 2x St37.0
3 2x
25
3x45°
195 80
8 2x Bogen 90-3-42,4x2,6 DIN 2605-2 ELBOW St37.0 弯管

其余 ▽

30° 15 G3/4 9 1:1 K2 R21

25 50 5° 3 2x 1:5 t=30 195

SCHWEIßVORSCHRIFTEN FERTIGUNGSVORSCHRIFTEN SN 200, TEIL 3 BEACHTEN	
BENAUIGKEITSGRAD FÜR MAßE OHNE TOLERANZANGABE	B UND F DIN 8570
ALLE NICHT BEMAßTEN KEHLNÄHTE	a = 8 (3) mm
SPANNUNGSARMGEGLÜHT	JA/NEIN
BETRIEBSDRUCK	BAR
DRUCK- UND DICHTGEPRÜFT DURCH INNENDRUCKVERSUCH NACH DIN 50104	JA/NEIN BAR
BEWERTUNGSGRUPPE DER SCHWEIßVERBINDUNG AN TEIL	DIN 8563 TEIL 3
BESONDERER SCHWEIßZUSATZWERKSTOFF	
TEIL NR. VORGEWÄRMT AUF	°C
BESCHEINIGUNG ÜBER MATERIALPRÜFUNG AN TEIL ERFORDERLICH	DIN 50049 -
ZWISCHENPRÜFUNG ERFORDERLICH	JA/NEIN
BESONDERE ABNAHMEPRÜFUNG ERFORDERLICH (S. ZEICHNUNGSEINTRAGUNG)	JA/NEIN

WELDING CODE OBSERVE MANUFACTURING INSTRUCTIONS SN 200, PART 3	
DIMENSIONAL ACCURACY REQUIRED FOR DIMENSIONS WITHOUT TOLERANCES	B AND F DIN 8570
ALL FILLET WELDS FOR WHICH NO DIMENSION IS SHOWN	a = 8 (3) mm
HEAT-TREATMENT FOR STRESS-RELIEVING	YES/NO
OPERATING PRESSURE	BAR
PRESSURE AND LEAK TEST BY INTERNAL PRESSURE TEST IN ACCORDANCE WITH DIN 50104	YES/NO BAR
CLASSIFICATION GROUP OF WELDED JOINT ON PART	DIN 8563 PART 3
SPECIAL FILLER METAL	
PART NO. PREHEATED UP TO	°C
CERTIFICATE OF MATERIAL TEST ON ITEM REQUIRED	DIN 50049 -
INTERMEDIATE TEST REQUIRED	YES/NO
SPECIAL INSPECTION REQUIRED (SEE NOTE ON DRAWING)	YES/NO

Pos.	Benennung	Abmessungen	Werkstoff		Menge	Einzel	Gesamt	Bemerkungen
01.10	扭销头 B2	TK309-90	Q235-A		2	0.2	0.4	
01.9	钩头	74/6522/1160.01.10	a 235-A		6	0.1	0.6	销同件
01.8	弯头 90-42×25	SD2844468-86	20		2	0.11	0.22	
01.7	管 ø42×25-222	"	"		2	0.7	1.4	"
01.6	管 ø42×25-80	"	"		2	0.24	0.48	"
01.5	管 ø60×3-1248	0522/1160.01.5	无缝管 20		1	0.4	0.4	元圆
01.4	三通 60×29-42×26	TK275-85	三G 25		2	0.1	0.2	
01.3	板 70×175 X370	0522/1160.01.3			2	28	56	元圆
01.2	板 50×270 ×500	"	"		1		55	
01.1	板 80×610 ×1250	74/6522/1160.01.1	钢板 16Mn		1		270	
01	11.13H轧机固定梁	0522/1160	焊接件					
序号	名称 规格 代号	材料	单重	总重	备注			

技术要求
1. 序号 1.2.3 组焊后加工所有加工面 最后焊接

| | | | | |